

1680 MiniBrera - LED - street type

Housing: in die-cast aluminium. Closing hooks are made of die-cast aluminium with retractable safety screws and AISI 304 stainless steel springs.

Optics: in PMMA, highly resistant to temperature and UV radiation

Diffusers: in tempered glass, 5 mm thick, resistant to thermal and mechanical shock (UNI EN 12150-1/2001).

Equipment: automatic temperature control device. In the event of an unexpected temperature rise caused by particular weather conditions or LED malfunctioning, the system will reduce the drive current as the LED gets warmer, reducing the lamp's operating temperature and guaranteeing proper operation. Supplied with a safety diode to protect against peak loads.

LED 4000K - 700mA - 7080lm - 47W, Ta-30+40°C life 80.000h 80% L80B20

Photobiological safety class: exempt group

At request it can be equipped with several dimming systems installed on the fixture:

- Bi-power dimming with virtual midnight option.

- Power line carrier (PLC) remote control.

- 1-10V dimmable driver with external control.

Regulations: Produced according to applicable EN60598-1 CEI 34-21 standards, degree of protection according to EN 60529 standards.

Wind surface: 800cm².

Download

DXF 2D

- 1680.dxf

3DS


- disano_1680_mini_brera.3ds

3DM

- disano_1680_mini_brera.3dm

Montaggi

- 1680.pdf



Code	Gear	Kg	Watt	Base	Lamps	Colour
325350-00	CLD CELL	6,91	LED white 47W		7080lm @ 700mA-4000K -CRI 70	GRAPHITE

Posts



- 1508 fluted pole ø120 with



- 1509 fluted pole ø120



- 1491 poles to be sunk into the



- 1493 pole with base



- 1430 City Pole



- 1416 poles to be sunk into the ground ø159



- 1415 pole with base ø159



- 1435 Village Pole